



WOOD

When it comes to the authenticity of a natural product, nothing can rival the beauty of wood. For any commercial application where function must be matched by style, such as offices, stores or hotels, wood is the statement choice.

Natural quality and technical innovation

With over 120 years of experience, Tarkett has developed in-depth expertise in the properties and qualities of wood, ensuring that our products offer the best possible construction techniques and surface treatments. Our wood collections combine extremely stable construction with strong locking systems and one of the hardest lacquer finishes on the market. The result is a collection that matches high-quality looks with unbeatable performance.

| | |
|---------------------------------|------------|
| Privilege | p. 266-267 |
| Epoque | p. 268-269 |
| Salsa/Bravo/ Professional 22 | p. 270-273 |
| Tango/Rumba | p. 274-275 |

Making the most of nature's own designs

Tarkett's innovative and environmentally friendly techniques add a new dimension to wood's wonderful natural qualities and colours. Spanning from almost white and grey to the deeper shades of heat-treated European wood species that mimic exotic varieties, our wood collection offers everything from classic to contemporary.

Naturally sustainable

Our wood collections are environmentally friendly through and through, from growing and harvesting, through manufacturing to eventual recycling.

To ensure constant and continuing supplies, we must look after our forests and harvest them with care. This is particularly important for tropical hardwoods, which are often over-exploited or illegally harvested. That's why all the wood we use – including hardwoods – comes only from sources with guaranteed replanting and harvesting with minimal waste.

Our production processes are designed to minimise the use of resources and, wherever possible, to recycle and reuse water, energy and waste material. ISO 9001 and 14001 certifications recognise the quality of our management systems and the efforts we make to ensure that our production processes respect people and the environment. We also have Forest Stewardship Council Certification (FSC) and the Swan eco-label for our products.

WOOD



- ┆ Real wooden floors for homes, shops, hotels, restaurants, offices and nursing homes
- ┆ Wood floors in a variety of wood species, patterns and stains to meet a variety of design needs
- ┆ Different lengths, widths and thicknesses for flexible use
- ┆ A very stable multi layer construction that minimize movement to variations in relative humidity
- ┆ High durability, good acoustic, good thermal stability and long life expectancy makes a wood floor an excellent choice for commercial application
- ┆ Wooden floors suitable for self regulating under floor heating systems (max 27°C)
- ┆ Proteco – the strongest surface protection on the market today – provided in glossy and matt lacquer and in hardwax oil.
- ┆ Easy to care & maintain without use of solvent based detergents
- ┆ Easy, fast and safe installation with glue free locking systems
- ┆ Extensive range of accessories to support installation, care & maintenance and accessories like smart skirting, mouldings and pipe covers in different wood species to complete the final touch of wood flooring.
- ┆ Wood is a natural and renewable material that Tarkett sources from forests and areas that are PEFC or FSC certified or meet our very strict demands on sustainable forestry.



| Technical data | | Privilege | Epoque | Salsa | Bravo | Professional | Tango | Rumba | |
|--|---|---|--|--------------|-------------------------------|-------------------------------|----------------------------|--------------|--|
| Thickness | - | 10 mm | 14 mm | | | 22 mm | 13 mm | | |
| Width | - | 70/90 mm | 117/162/190/ 200 mm | 188/192 mm | 188 mm | 188 mm | 162/190 mm | 188 mm | |
| Length | - | 490/600/ 900 mm | 1075/1245/ 2000-2520 mm | 2272/2525 mm | 2525 mm | 2525 mm | 2000-2520 mm | 1250/2525 mm | |
| Wearlayer thickness | - | app. 3.6 mm | | | | | app. 2.5 mm | | |
| Weight | - | 7.3 kg/m ² | app. 8.0 kg/m ² | | | 14.8 kg/m ² | app. 7.2 kg/m ² | | |
| Taber abraser/ Lacquer's wear resistance* | prEN 13696 | > 2500 app. 3.5 mg/100 revs | > 4000 revs > 3500 revs app. 3.5 mg/100 revs | | | | | | |
| abrasion penetration Lacquer | | | | | | | | | |
| abrasion penetration Proteco Lacq. | | | | | | | | | |
| abrasion penetration Proteco Nat. abrasive wear | | | | | | | | | |
| Reduction of sound weighted index "footfall" to the room below. | NF EN ISO 140-8/Acc to NF EN ISO 717-2 | - | $\Delta L_w = 17$ dB with 3 mm Cellfoam | | | | | | |
| Formaldehyde emission | EN 13986 | | | | E1 | | | | |
| Reaction to Fire | EN 13501 | | | | D _n | | | | |
| Thermal insulation value | | RT = 0.100 m ² K/W | RT = 0.101 m ² K/W | | RT = 0.152 m ² K/W | RT = 0.101 m ² K/W | | | |
| board only | | | RT = 0.121 m ² K/W | | RT = 0.182 m ² K/W | RT = 0.121 m ² K/W | | | |
| with rag felt | | | RT = 0.191 m ² K/W | | RT = 0.252 m ² K/W | RT = 0.191 m ² K/W | | | |
| with 3 mm Cellfoam | | | | | | | | | |
| Underfloor heating compatible** | - | Maximum floor surface temperature 27 °C with self-regulating under-floor heat system Not compatible for Professional 22 mm | | | | | | | |

The above information is subject to modifications for the benefit of further improvement (01/2010).

For more detailed technical information, please contact Tarkett.

* Data show results with new components according to 2006 update. Method not applicable for brushed products due to the structured surface.

** Not suitable for the woodspecies beech and maple

Privilege 70-90 pages 266-267

Epoque pages 268-269

Salsa/Bravo/
Professional 22 pages 270-273

Tango/Rumba pages 274-275


Privilege



- ┆ Classic and stylish single-strip design meeting today's demands on function and aesthetics,
- ┆ Six different wood species; inside each wood, different grading and shades to choose from,
- ┆ 10 mm two-layer wood flooring for glue down application,
- ┆ Approximately 3,6 mm wear layer,
- ┆ Three lengths (490/600/900 mm) and two widths (70/90 mm),
- ┆ Surface protection by Tarkett 5Tech lacquer




| | |
|----------------------------|----------|
| Privilege 70/490 mm | 8712 100 |
| Privilege 70/600 mm | 8712 101 |
| Privilege 90/600 mm | 8713 100 |
| Privilege 90/900 mm | 8713 101 |



Iroko Superior



Privilege 70/490 mm
Privilege 70/600 mm
Privilege 90/600 mm
Privilege 70/900 mm




Oak Superior Light

7872 100
7872 101
7873 100
7873 101




Oak Superior Dark

7872 200
7872 201
7873 200
7873 201



Oak Classic


7872 300
7872 301
7873 300
7873 301



Steamed Beech


Privilege 70/490 mm
Privilege 70/600 mm

7928 100
7928 101




Cherry Superior

8569 100
8569 101



Cherry Classic


8569 300
8569 301



Doussie Superior Light


Privilege 70/490 mm
Privilege 70/600 mm
Privilege 90/600 mm
Privilege 90/900 mm

8704 100
8704 101
8705 100
8705 101




Doussie Superior Dark

8704 200
8704 201
8705 200
8705 201



Doussie Classic


8704 300
8704 301
8705 300
8705 301



Iroko Classic


Privilege 70/490 mm
Privilege 70/600 mm
Privilege 90/600 mm
Privilege 90/900 mm

8712 300
8712 301
8713 300
8713 301



Merbau Superior

8608 100
8608 101



Merbau Classic


8608 300
8608 301

Epoque



- ┆ Our most exclusive designs
- ┆ Offered in 1 and 2-strip boards
- ┆ 14 mm thick, with a wear layer of approx. 3,6 mm (can be re-sanded 4-5 times)
- ┆ Range of four widths: 117 mm, 162 mm, 190 mm and 200 mm, all except 200 mm with bevelled edges for a more exclusive feel
- ┆ Proteco Lacquer protection: lengthwise mini-bevel on each board in 162 mm width
- ┆ Proteco Natura protection: lengthwise maxi-bevel on each board in 162 mm width
- ┆ Proteco Hardwax Oil protection: lengthwise maxi-bevel on each board in 162 mm width
- ┆ User-friendly, glue-free locking system: T-Lock


Epoque 2-strip



Oak Nature


2 520 mm 7818 005 ●
2 520 mm 7818 008 ●

Epoque 190 Maxiplank



Oak

2 000 mm 7817 002 ●
2 520 mm 7817 003 ●
2 200 mm 7817 014 ●
2 520 mm 7817 015 ●



Epoque 117 Miniplank



Oak Nature

- 1 245 mm 7820 001 ●
- 1 075 mm 7820 004 ●
- 1 245 mm 7820 008 ●
- 1 075 mm 7820 009 ●



Beech Steamed

- 7907 001 ●
- 7907 002 ●



Merbau


- 8604 001 ●
- 8604 003 ●



Jatoba

- 1 245 mm 8638 001 ●
- 1 075 mm 8638 002 ●

Epoque 162 Maxi plank



European Oak

- 2 000 mm 7813 002 ●
- 2 200 mm 7813 001 ●
- 2 000 mm 7813 005 ●
- 2 200 mm 7813 004 ●
- 2 200 mm 7813 601 Oiled ●




American Oak

- 7815 012* ●
- 7815 001 ●
- 7815 002 ●
- 7815 003* ●




Ash Cognac

- 7976 201 ●
- 7976 202 ●




Beech Steamed

- 2 000 mm 7906 002 ●
- 2 200 mm 7906 001 ●
- 2 520 mm



Merbau

- 8602 002 ●
- 8602 001 ●



Jatoba

- 8637 002 ●
- 8637 001 ●
- 8637 003 ●

* 2 520 mm long

Salsa/ Bravo/ Professional 22

Salsa


- ┆ 14 mm thickness with wear layer of approx. 3.6 mm
- ┆ Versatile wood offer with 3-strip design
- ┆ Ultraloc or 2-lock locking system

Bravo

- ┆ 14 mm thickness with wear layer of approx. 3.6 mm
- ┆ 3-strip design with lively appearance
- ┆ Comes with Ultraloc or 2-lock

Salsa and Bravo can be re-sanded 4-5 times.





Salsa 3-strip



2 525 mm
2 525 mm
2 272 mm




Red Oak

7890 002 ●




Oak Select

7833 005 ●



Oak Nature

7833 001 ●
7833 002 ●
7870 005* ●




Oak Rustical

2 525 mm 7834 001 ●
2 525 mm 7834 002 ●
2 272 mm 7870 006* ●




Ash Nature

7954 001 ●
7954 002 ●



Maple Canadian Nature

8510 002 ●
8510 003 ●




Birch

2 525 mm 8538 001 ●
2 272 mm



Cherry

8563 001 ●
8571 001* ●



Beech Steamed

7914 005 ●




Beech Nature

2 525 mm 7914 001 ●
2 525 mm 7914 002 ●
2 272 mm 7931 002* ●



Beech Classic

7916 001 ●



Walnut

8583 003 ●
8583 002 ●
8577 001* ●

* Salsa with oiled finish comes with 2-lock system

Salsa/ Bravo/ Professional 22



2 272 mm

Salsa 3-strip/Fine Line Multi strip



Ash Cognac

7983 003 ●
7983 004 ●



Oak Fine Line

7870 008 ●

Basket Weave



2 525 mm 7806 002 ●




Oak



Walnut

8585 003 ●



| | | |
|----|--|--|
| CE | EN 14041:2004 | Manufactured by: Tarkett AB SE-289 89 Hanaskog SWEDEN |
| |  OS | EN 13489 Salsa/Bravo/Professional 22 |

| | | |
|--|--|--|
|  |  |  |
| ● | ● | ● |

Bravo 3-strip



2 525 mm




Oak

7835 001 ●
7835 002 ●




Maple Canadian

8511 001 ●




Birch

8539 001 ●



Cherry

8564 001 ●




Beech

7915 001 ●

Professional 22



2 525 mm



Oak Nature

7825001 ●



Ash Nature

7949 001 ●



Tango/Rumba


Tango

- ┆ 13 mm wooden floor with approx. 2.5 mm thick wear layer of real wood
- ┆ Comes as on plank flooring with bevelled edges (mini-bevel), with T-lock and Proteco lacquer.
- ┆ Two lengths available

Rumba

- ┆ 13 mm wooden floor with approx. 2.5 mm thick wear layer of real wood
- ┆ Comes with 3-strip design and Ultraloc.
- ┆ Different lengths available.
- ┆ Tango and Rumba can be re-sanded 2-3 times.





Tango 162 Plank



Oak Nature

- 2 000 mm 7849 001 ●
- 2 200 mm 7849 002 ●
- 2 520 mm 7849 003 ●

Tango 190 Plank



Oak Nature

- 7851 001 ●
- 7851 002 ●
- 7851 003 ●

Rumba 3-strip



Oak Nature

- 2 525 mm 7800 007 ●
- 2 525 mm 7800 008 ●
- 1 250 mm 7800 014 ●




Oak Robust

- 7801 001 ●



Ash Nature

- 7941 003 ●
- 7941 004 ●




Beech Nature

- 2 525 mm 7900 009 ●



Beech Classic

- 7901 002 ●



Merbau

- 8600 005 ●